

X-15



▶ FEATURES

- Distinctive aluminum alloy housing for added strength
- NeoV Optical Glass™
- Swift 12ms response time
- High 400 brightness
- Crisp 500 contrast ratio
- DVI ready for high quality signal
- S-Video* and CVBS* inputs
- Auto-adjustment for optimal setting
- Kensington® security slot
- VESA standard wall mount
- Available colors: black, white

▶ SPECIFICATION

Panel	Panel Type	TFT LCD
	Panel Size	15.0" (381mm)
	Max. Resolution	XGA 1024 x 768
	Pixel Pitch	0.297mm
	Brightness	400cd/m ² (Typical)
	Contrast Ratio	500:1 (Typical)
	Surface Treatments	Hard Coating (3H), Anti-glare Treatment
	Viewing Angle (H/V)	140°/130° (Typical)
	Display Color	16.7M
	Response Time	12ms (GTG)
Input	Frequency (H/V)	H: 30kHz - 60kHz V: 50Hz - 75Hz
	Max. Pixel Clock	80MHz
	Life Time	50,000hrs (Minimum)
	Analog	15-Pin D-Sub
Connector	Digital	29-Pin DVI-D
	S-Video*	4-Pin Mini Din S-Video
	CVBS*	CVBS Jack
	Power	3-Pin AC Plug
NeoV Optical Glass	Thickness	3.0mm (0.18")
	Reflection Rate	<1%
	Transmission Rate	>96%
	Hardness	>6H (MOH's Rating)
Tilt	Tilt	0° ~ +20°
Mounting	VESA FPMPI	Yes (100mm)
Regulation Approval	Safety & EMI	FCC, UL/CUL, EPA, CE, TUV/BAURT, TCO 95, BSMI, CB, ISO 13406-2
	VESA	DDC 1/2B, DPMS
	Power AC Consumption	100 - 240V, 50 - 60Hz <48W (On) <4W (Stand-by) <2W (Off)
Power	Net (W x H x D)	380 x 359 x 155mm (15.0" x 14.1" x 6.1")
	Packing (W x H x D)	445 x 490 x 225mm (17.5" x 19.2" x 8.9")
Dimensions	Net Weight	4.8Kg (10.6lbs)
	Gross Weight	7.0Kg (15.4lbs)
Weight	1 Pallet	40 Cartons
	20' Container	480 Sets
	40' Container	1040 Sets

*Video inputs are optional functions

All specifications are subject to change without prior notice

