

▶ 17" LCD DISPLAY

X-17AV/X-17STD



▶ FEATURES

- Distinctive aluminum alloy housing for added strength
- NeoV Optical Filter™
- High 500 contrast ratio
- 170° wide viewing angle
- DVI* ready for high quality signal
- S-Video* and CVBS* inputs
- Auto-adjustment for optimal setting
- Kensington® security slot
- VESA standard wall mount



▶ SPECIFICATION

Panel	Panel Type	TFT LCD	
	Panel Size	17.0" (432mm)	
	Max. Resolution	SXGA 1280 x 1024	
	Pixel Pitch	0.264mm	
	Brightness	250cd/m ² (Typical)	
	Contrast Ratio	500:1 (Typical)	
	Surface Treatments	Hard Coating (3H), Anti-glare Treatment	
	Viewing Angle (H/V)	170°/170° (Typical)	
	Wide Viewing Angel	Yes	
	Display Color	16.7M	
Input	Response Time (R/F)	15ms/10ms (Typical)	
	Frequency (H/V)	H: 30kHz - 80kHz V: 50Hz - 75Hz	
	Max. Pixel Clock	135MHz	
	Life Time	50,000hrs (Minimum)	
	Connector	Analog	15-Pin D-Sub
		Digital*	29-Pin DVI-D
		S-Video*	4-Pin Mini Din S-Video
		CVBS*	CVBS Jack
	NeoV Optical Filter	Power	3-Pin AC Plug
		Thickness	3.0mm (0.18")
Reflection Rate		<1%	
Transmission Rate		>96%	
Tilt	Hardness	>6H (MOH's Rating)	
	Tilt	0° ~ +15°	
	Mounting	VESA FPMPI Yes (100mm)	
Regulation Approval	Safety & EMI	FCC, UL/CUL, EPA, TUB/BAURT, CE, NORDIC, TCO 95, NUTEK, BSMI, VCCI, CCC, CB, ISO 13406-2	
	VESA	DDC 1/2B, DPMS	
	Power	Power AC Consumption	100 - 240V, 50 - 60Hz <48W (On) <5W (Stand-by) <5W (Off)
Dimensions		Net (W x H x D)	408 x 398 x 175mm (16.1" x 15.7" x 6.9")
		Packing (W x H x D)	495 x 510 x 228mm (19.5" x 20.0" x 9.0")
Weight	Net Weight	6.8Kg (13.9lbs)	
	Gross Weight	9.5Kg (20.9lbs)	
Packing	1 Pallet	40 Cartons	
	20' Container	400 Sets	
	40' Container	880 Sets	

*Video and DVI functions are only available on X-17AV

All specifications are subject to change without prior notice.