

▶ 19" LCD DISPLAY

X-19AV/X-19STD



▶ FEATURES

- Distinctive aluminum alloy housing for added strength
- NeoV Optical Filter™
- Crisp 700 contrast ratio
- Super wide viewing angle technology
- DVI* ready for high quality signal
- S-Video* and CVBS* inputs
- Auto-adjustment for optimal setting
- Kensington® security slot
- VESA standard wall mount



▶ SPECIFICATION

Panel	Panel Type	TFT LCD
	Panel Size	19" (483mm)
	Max. Resolution	SXGA 1280 x 1024
	Pixel Pitch	0.294mm
	Brightness	250cd/m ² (Typical)
	Contrast Ratio	700:1 (Typical)
	Surface Treatments	Hard Coating (2H), Anti-glare Treatment
	Viewing Angle (H/V)	170°/170° (Minimum)
	Uni-Directional	160° (Typical)
	Display Color	16.7M
Input	Response Time (R/F)	15ms/10ms (Typical)
	Frequency (H/V)	H: 30kHz - 80kHz V: 50Hz - 75Hz
Connector	Max. Pixel Clock	135MHz
	Life Time	40,000hrs (Typical)
	Analog	15-Pin D-Sub
	Digital*	29-Pin DVI-D
NeoV Optical Filter	S-Video*	4-Pin Mini Din S-Video
	CVBS*	CVBS Jack
	Power	3-Pin AC Plug
Tilt	Thickness	3.0mm (0.18")
	Reflection Rate	<1%
	Transmission Rate	>96%
Mounting	Hardness	>6H (MOH's Rating)
	Tilt	0° ~ +15°
Regulation Approval	VESA FPMPMI	Yes (100mm)
	Safety & EMI	FCC, UL/CUL, EPA, TUV/BAURT, CE, NORDIC, TCO 95, NUTEK, BSMI, VCCI, CCC, CB, ISO 13406-2
Power	VESA	DDC 1/2B, DPMS
	Power AC Consumption	100 – 240V, 50 – 60Hz <48W (On) <5W (Stand-by) <5W (Off)
Dimensions	Net (W x H x D)	444 x 419 x 175mm (17.5" x 16.5" x 6.9")
	Packing (W x H x D)	540 x 525 x 228mm (21.2" x 20.7" x 9.0")
Weight	Net Weight	7.9Kg (17.4lbs)
	Gross Weight	10.7Kg (23.6lbs)
Packing	1 Pallet	40 Cartons
	20' Container	400 Sets
	40' Container	800 Sets

*Video and DVI functions are only available on X-19AV

All specifications are subject to change without prior notice.

www.agneovo.com

Copyright © 2004 AG Neovo. All rights reserved.
The name AG Neovo is a trademark of Associated Industries China, Inc.
All other trademarks are the property of their respective owners.